

TM-1000 TM-2000



Flat LCD Touch Monitors



TM-1000 AND TM-2000 TOUCH MONITORS

With a small footprint, the TM-1000 and TM-2000 touch monitors are especially attractive and space efficient in POS applications. The large bright display is adjustable for clear viewing in high or low light environments and the touch interface increases accuracy and improves operator efficiency. Cables and connectors are easy to access, yet safe and secure from interference.

SPECIFICATIONS

	TM-1000	TM-2000
Display Type:	Active Matrix TFT LCD	
LCD Size:	13.3"	15.1"
Display Area:	11.2" x 8.4" 284mm x 215mm	12" x 9" 304mm x 228mm
Monitor Dimensions:	13.3"W x 13.7"H x 9.8" D 342W x 351H x 250mmD	15.3"W x 13.8"H x 9.8" D 393W x 355H x 250mmD
Highest Resolution:	1024 x 768	
Colors:	16.7 Million	
Brightness:	150 cd/m2	250 cd/m2
Contrast Ratio:	200 : 1	350 : 1
Adjustable Angle:	70° to 240°	
Viewing Angle:	H = 90° V = 50°	H = 150° V = 140°
Input Signal:	RGB Analog	
Input Connector:	D-Sub 15 Pin Female	
Power Supply:	2.5A 12V External Adapter	
Power Consumption:	20W Maximum	25W Maximum
Temperature:	32° to 114°F (0° to 40°C)	
Humidity:	10% to 90%	
Touch Panel:	Resistive or Capacitive Type	
MSR:	PS/2 K/B	
Wall Mount Bracket:	Standard	

TM-1000/2000



Flip Down Door Protects
Liquid Resistant Control Panel



Optional MSR



Tiltable Display



Available in Dark Gray and Ivory

Cover Photo
TM-1000 and TM-2000 with optional MSR.

All trademarks and copyrights acknowledged.
All features/specifications subject to change without notice.
Printed in U.S.A.